



Shenzhen Feasycom Technology Co.,LTD

www.feasycom.com

Address: Rm 2004-2005, 20F, Huichao Technology Bldg, Jinhai Rd,
Xixiang, Baoan Dist, Shenzhen, 518100, China.

FeasyBeacon Super

FSC-BP109

Bluetooth Long Range Beacon

Datasheet Version 1.5



FeasyBeacon Super BP109 is an USB-powered Bluetooth 4.2 super long range beacon, which comply with iBeacon, Eddystone, AltBeacon technology. With innovative “FeasyBeacon” APP work via iOS and Android System, support 10 slots broadcast advertising frames. Transmit distance reach up to 4000m in very open space.

FeasyBeacon Super BP109 with CSR8811 Chipset, is specially customized for solving the poorer coverage problem, suitable for, stadium, museum, exhibition, hotel, restaurant and the remote area wireless communication application, etc.

FeasyBeacon Super BP109 can be powered by any electronic device with USB port or directly by the AC power via an AC/DC power supply with the USB Port. This ensures an endless operating life, without any maintenance & extra cost for battery replacement.

FCC,CE, ROHS Certification available.

| Advertising Specification | |
|----------------------------------|---|
| Advertising Format | Eddystone (URL/ UID/ TLM/ EID), iBeacon, AltBeacon |
| Config App | FeasyBeacon (Free for lifetime using) |
| APP Pin Code | 000000 |
| Advertising Interval | 100ms-1200ms |
| Secure Config | access password |
| Max Number of Broadcast | 10 Slots configurable advertising frames |
| Default Broadcast Interval | 150ms for iBeacon & Eddystone |
| Support System | iOS 7.0+, Android4.3+ |
| Work Distance | In open area: iOS System: 4000m Android System : 1000m |
| Upgrade Mode | OTA (over the air update firmware) |
| Product Specification | |
| Model | BP109 |
| TX power | +18.5 dBm (Max) |
| Power Supply | 5V USB |
| Core Module | CSR8811 + RF Power Amplifier |
| MCU Core | ST ARM 32-bit Cortex-M4 CPU |
| Current Consumption | Radio TX: 225 mA (@ 18.5dBm) |
| Bluetooth Standard | Bluetooth 4.2 Version |
| Frequency Band | 2.402 to 2.480 GHz (according Bluetooth 4.0 specifications, worldwide ISM band) |
| Antenna Type | Whip Antenna (SMA interface) |
| Radiation Diagram | Omni-directional |
| Material | ABS plastic |
| Color | Black |
| Size | 9 X 3.8 X 2.2 cm(not including antenna) |
| Net Weight | 54g |
| Packing Size | 22.5*8.5*3cm |
| Protection | IP40 |
| Operating Temperature | -40°C to +85°C |
| Certification | CE, ROHS, FCC |

Feasycom reserves the right to change product specifications at any time without prior notice.

iBeacon is a trademark of Apple Inc., Eddystone is a trade of Google Inc.